

IN THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application. Please cancel claims 1 and 6 without prejudice and amend claims 2, 4, 7 and 9 as follows:

1. (Cancel).
2. (Currently Amended) ~~[[The]]~~ A data recording/reproducing device as set forth in claim 1 adapted for recording and/or reproducing data by an optical recording system with respect to a disc-shaped recording medium,
the data recording/reproducing device comprising:
recording/reproducing means for recording and/or reproducing the data;
deterioration information detecting means for detecting deterioration of the disc-shaped recording medium;
display means for displaying deterioration information of the disc-shaped recording medium; and
control means for performing a control to generate deterioration information indicating deterioration in accordance with the detected deterioration to conduct a display on the display means in accordance with the deterioration information,

wherein the deterioration information detecting means detects read error frequency in reading out address information on the disc-shaped recording medium to generate first deterioration information from the read error frequency, and the control means generates second deterioration information when the first deterioration information is above a predetermined threshold value.

3. (Original) The data recording/reproducing device as set forth in claim 2,
wherein address information on the disc-shaped recording medium is ATIP (Absolute
Time In Pregroove).
4. (Currently Amended) ~~[[The]]~~ A data recording/reproducing device as set forth in claim 1
adapted for recording and/or reproducing data by an optical recording system with respect to a
disc-shaped recording medium,
the data recording/reproducing device comprising:
recording/reproducing means for recording and/or reproducing the data;
deterioration information detecting means for detecting deterioration of the disc-shaped
recording medium;
display means for displaying deterioration information of the disc-shaped recording
medium; and
control means for performing a control to generate deterioration information indicating
deterioration in accordance with the detected deterioration to conduct a display on the display
means in accordance with the deterioration information,

wherein the deterioration information detecting means detects error frequency of data to
which a predetermined error correction encoding has been implemented and recorded on the
disc-shaped recording medium to generate first deterioration information from error frequency of
the recorded data, and the control means serves to generate second deterioration information
when the first deterioration information is above a predetermined threshold value.

5. (Original) The data recording/reproducing device as set forth in claim 4, wherein the error correction encoding is performed by using CIRC (Cross-Interleaved Reed-Solomon Code).
6. (Cancel).
7. (Currently Amended) ~~[[The]] A data recording/reproducing method as set forth in claim 6 of recording and/or reproducing data by an optical recording system with respect to a disc-shaped recording medium,~~
the data recording/reproducing method comprising the steps of:
a deterioration detection step of detecting deterioration of the disc-shaped recording medium in recording and/or reproducing the data; and
a control step of performing a control to generate deterioration information indicating deterioration in accordance with the detected deterioration to conduct a display on display means in accordance with the deterioration information,
wherein, at the deterioration information detection step, read error frequency in reading out address information on the disc-shaped recording medium is detected so that first deterioration information is generated from the read error frequency, and at the control step, second deterioration information is generated when the first deterioration information is above a predetermined threshold value.
8. (Original) The data recording/reproducing method as set forth in claim 7,
wherein address information on the disc-shaped recording medium is ATIP (Absolute Time In Pregroove).

9. (Currently Amended) ~~[[The]] A data recording/reproducing method as set forth in claim 6 of recording and/or reproducing data by an optical recording system with respect to a disc-shaped recording medium,~~

the data recording/reproducing method comprising the steps of:
a deterioration detection step of detecting deterioration of the disc-shaped recording medium in recording and/or reproducing the data; and
a control step of performing a control to generate deterioration information indicating deterioration in accordance with the detected deterioration to conduct a display on display means in accordance with the deterioration information,

wherein, at the deterioration information detection step, error frequency of data to which a predetermined error correction encoding has been implemented and recorded on the disc-shaped recording medium is detected, and, at the control step, first deterioration information is generated from error frequency of the recorded data, and second deterioration information is generated when the first deterioration information is above a predetermined value.

10. (Original) The data recording/reproducing method as set forth in claim 9, wherein the error correction encoding is performed by using CIRC (Cross-Interleaved Reed-Solomon Code).

11. (Original) A digital camera adapted for recording and/or reproducing data by the optical recording system with respect to a disc-shaped recording medium,
the digital camera comprising:

image pick-up means for picking up an image of an object;

image processing means for processing image data which has been picked up by the
image pick-up means;

recording/reproducing means for recording and/or reproducing the image data with
respect to the disc-shaped recording medium;

deterioration information detecting means for detecting deterioration of the disc-shaped
recording medium;

display means for displaying deterioration information of the disc-shaped recording
medium, and

control means for performing a control to generate deterioration information indicating
deterioration in accordance with the detected deterioration to conduct a display on the display
means in accordance with the deterioration information.

12. (Original) The digital camera as set forth in claim 11,

wherein the deterioration information detecting means detects read error frequency in
reading out address information on the disc-shaped recording medium to generate first
deterioration information from the read error, and the control means generates second
deterioration information when the first deterioration information is above a predetermined
threshold value.

13. (Original) The digital camera as set forth in claim 12,

wherein address information on the disc-shaped recording medium is ATIP (Absolute
Time In Pregroove).

14. (Original) The digital camera as set forth in claim 11,
wherein the deterioration information detecting means detects error frequency of data to which a predetermined error correction encoding has been implemented and recorded on the disc-shaped recording medium to generate first deterioration information from error frequency of the recorded data, and the control means generates second deterioration information when the first deterioration information is above a predetermined threshold value.
15. (Original) The digital camera as set forth in claim 14,
wherein the error correction encoding is performed by using CIRC (Cross-Interleaved Reed-Solomon Code).